

indo green[®] PP-R

The latest, cost effective and reliable plumbing system for Hot and Cold water



Supreme industries has evolved to become an undisputed leader in India's plastics industry, with valuable experience in providing innovative and cost effective piping solution. Supreme a name synonymous with quality, innovation and service is trend setters in plastic piping system in India. Company's objective is to meet the growing needs of the customers in water management and housing sector through specially developed high performance piping range. The comprehensive and exclusive range of Supreme plastic pipe systems are designed and manufactured to meet the highest standards set by the building and construction industry across the world. Supreme has, no doubt, brought about a revolution in the Indian plastic pipe industry.

Supreme is pioneer in introducing PP-R piping system in India with indigenously manufactured complete range of pipes and fittings with necessary heating tools and accessories. Supreme indo green PP-R is made from PP-R type-3 supplied by reputed European suppliers which have bodycote certification. Only indo green is approved and listed by reputed WRAS, UK in the country which ensures its superiority and suitability for drinking water application.

Jeevan bhar ka saath...

THE SYSTEM

Supreme indo green PP-R is designed for hot and cold water application and it is the latest and most suitable system for all plumbing applications. Besides plumbing, this system can be used for varieties of applications like air distributions, radiator heating etc. The specific chemical structure of indo green PP-R provides the well balanced mechanical properties and superior long term heat resistance. The system is in use for more than 20 years in Europe, the Gulf, China and Russia, and gaining good acceptance across the world. Supreme indo green is the only system which comes with 10 years warranty. Indo green pipes are approved and listed by WRAS (Water Regulations Advisory Scheme), Uk. Indo green PP-R is the most suitable and ideal solution for housing sector.

MATERIAL PROPERTIES

- Density at 23 °C : 0.909 g/cm³
- Softening temperature : 131.3 °C
- E - modulus : 808 Mpa
- Coefficient of thermal conductivity : 0.21 W/m °C
- Impact strength : 23 °C - No break, 0 °C - 160 KJ/m²
- Coeff. of linear thermal expansion : 0.12 mm/m °C

FIELDS OF APPLICATION

Indo green PP-R is designed for hot and cold water supply and heating applications and it is suitable for different applications enlisted below.

- Hot and cold water supply in residential, industrial, commercial and public projects
- Solar heater applications
- Drinking water and liquid foods
- Watering systems for greenhouses and gardens
- Transportation of aggressive fluids
- Water purifying plants
- Radiator heating
- Traditional heating systems
- Air distribution and compressed air systems
- Chilled water and air conditioning

FEATURES AND BENEFITS

Light weight, easy and quick assembly - which results in extensive saving on time and labour.

Safest system for carrying drinking water - PP-R is absolutely free from corrosion and negative biological effects. It does not break down even under the harshest of water conditions, hence the quality of water never deteriorates. It is in full compliance with the International standards on the use of plastics materials for the transportation of potable water.

Excellent resistance to corrosion and chemical attacks - PP-R pipes and fittings are stable against the majority of known aggressive and toxic chemicals, aggressive soils and fluids in the external environment.

Reduced head loss - Mirror smooth inside surface ensures high flow rates and very low frictional losses.

Low thermal conductivity - which results in saving on insulation cost, thereby reducing overall operational costs.

Free from scaling - Due to the unique properties like extremely smooth surface, non-polar nature of the material, and low surface energy of the PP-R, limestone or other deposits cannot form and hence there is no scaling or blockage in the pipelines, throughout the life of the piping system.

High impact strength - Indo green PP-R has a very good impact strength.

Low on sound - The sound-dampening property is a major attraction in plumbing, flushing and pressurized flow applications.

Long operational durability - Indo green system ensures a minimum 50 years of trouble free performance.

Overall Economy - This system is most cost effective than any other plumbing system. Moreover, due to savings in installation and insulation costs, this system is even comparable with standard make G.I. B class piping system.

Besides above stated benefits, it has very good resistance to frost, abrasion and stray current, and is considered to be most suitable in seismic areas.

Pipe Dimensions as per IS 15801 specifications

Nominal Size (mm)	Outer Diameter (D) in mm		SDR-11		SDR-7.4		SDR-6	
			Wall Thickness (t) in mm		Wall Thickness (t) in mm		Wall Thickness (t) in mm	
	Minimum	Maximum	Minimum	Maximum	Minimum	Maximum	Minimum	Maximum
20	20.0	20.3	1.90	2.30	2.80	3.30	3.40	4.00
25	25.0	25.3	2.30	2.80	3.50	4.10	4.20	4.90
32	32.0	32.3	2.90	3.40	4.40	5.10	5.40	6.20
40	40.0	40.4	3.70	4.30	5.50	6.30	6.70	7.60
50	50.0	50.5	4.60	5.30	6.90	7.80	8.30	9.40
63	63.0	63.6	5.80	6.60	8.60	9.70	10.50	11.80
75	75.0	75.7	6.80	7.70	10.30	11.60	12.50	14.00
90	90.0	90.9	8.20	9.30	12.30	13.80	15.00	16.70
110	110.0	110.9	10.00	11.20	15.10	16.90	18.30	20.40
160	160.0	161.5	14.60	16.30	21.90	24.30	26.60	29.50

Note : 1. Pipes are offered in Indo green (IG) colour with standard length of 3.0 meter, duly packed in plastic bags. 2. Non standard length of 4.0 meter and 6 meter can be offered against bulk requirements. 3. All dimensions unless otherwise specified are in mm. 4. 160mm pipe is offered as per ISO 15874

FITTINGS



Coupler



Elbow 90°



*Reducing Elbow



Elbow 45°



Equal Tee



*Reducing Tee



Cross Tee



*Reducer Male/Female



Reducer Female/Female



End Cap



Female Threaded Elbow 90°



Female Threaded Elbow 90° with supporting device



Male Threaded Elbow 90°



Female Threaded Tee



Male Threaded Tee



Female Threaded Joint (FTA)



Male Threaded Joint (MTA)



M.T.A. (Plastic)



Union



Union - Female Threaded



Union - Male Threaded



All Plastic Weld in Saddle



Weld in Saddle - Female Threaded



Weld in Saddle - Male Threaded



Adapter with Integral Flange



Flange Adapter



Flange



Metal Flange



Metal Clamp with Rubber Seal (F)



Pipe Clip (Plastic)



Ball Valve



Screw Tap with Handwheel



Concealed Valve



Circuit Testing Plug (Moulded)



Threaded Plug



Hole Repairing Plug



Tank Connector



Expansion Loop (F)



Bend 90° (F)



Short Bend (BW)



Bypass Bend (F)



Offset Bend (F)



Polyfusion Device SPD 2600



Polyfusion Device SPD 3800



Polyfusion Device SPD 41200



Polyfusion Device 90° (Rod type) SPD 5600



Heating Plate for Butt Welding SPD 61800



Matrices-Paired



Matrices-Non-Paired



Matrices for Weld in Saddle



Hole Repairing Matrices



Drill Bit for Weld in Saddle



Mounting Stand (for PFD)



Pipe Scraper



Pipe Cutter (European make)



Rotating Cutter



Assembly Jig



Butt Welding Machine

THERMAL EXPANSION OF THE SYSTEM

In PP-R, deformation due to expansion are absorbed due to "low elastic modulus" of the pipe material. Therefore no real problems are envisaged due to expansion in concealed installations.

In case of external applications on ceiling or walls, where long lengths are installed, the effects of expansion contractions shall be considered while assembly of indo green system. This problem can be solved either by using suitable expansion loops or clamps. (for more detail please refer to our assembly regulation manual)

HEAT LOSS AND INSULATION REQUIREMENTS

Due to the low thermal conductivity of indo green PP-R (0.21 W/mK) normally it may not be necessary to insulate, when used for hot water concealed application. However, for application where central boiler is used for distribution of hot water, and the circulation of hot water being continuous, it is necessary to insulate distribution lines to prevent excessive loss of heat and energy wastage.

POLYFUSION WELDING

Joints of the indo green pipes and fittings are usually jointed together by poly-fusion welding, which is a fundamental property of this system. This process consists of mixing of melted material of external surface of the pipe and internal surface of the fitting, after heating them up to 260 °C to 280 °C on the small welding machine called poly-fusion device. Properly made welded joint, when cut through, shows no traces of contact surface between two elements i.e. pipe and fitting in the entire volume of joint. Thus fusion process gives homogeneous, integral, long lasting, leak proof joints.

JOINING PROCEDURE



Cutting - Cut the pipe square to the required length by cutter. Deburr the cut end if necessary. Pipe ends must be clean cut at right angles.

Cleaning - Prior to welding, the pipe and fitting should be dried and properly cleaned.

Marking - Mark the required insertion depth (welding depth) on the pipe with the help of suitable marker.

Heating - Ensure that the indicator light on the welding device signals that the device is hot enough (260-270 °C) for welding. First weld can be made after 5 minutes when heating light gets off. Heat the pipe and fitting on the polyfusion device as per the recommended heating times. (The heating time starts, when pipe and fitting have been pushed to the correct welding depth on the matrices.) While heating the pipe and fitting in the matrices, apply slight pressure from both sides.

Welding - After specified heating time, remove the pipe and fitting out of the matrices. Heated end of pipe should be pushed in to the flared end of the hot fitting down to the previously marked depth. Do not turn or twist the pipe or fitting while pushing in to the matrices and pulling out of the matrices.

Cooling - After the specified cooling time, the joint gets a first stiffness, after this phase next joint can be made.

CONCEALED WORK While doing concealed bathroom work, it is easier to make the required network on floor by proper measurement of different pipe lengths. To avoid misalignment, guiding marks on pipes and fittings should be referred.

Polyfusion welding times according to DVS 2207 norms

Pipe Size (mm)	16	20	25	32	40	50	63	75	90	110
Heating time (min) seconds	5	5(3)*	7(4)	8(4)	12(6)	12(9)	24(12)	30(15)	40(20)	50(25)
Working time (max) time of removal, seconds	4	4	4	6	6	6	8	8	8	10
Cooling time (min) minutes	2	2	2	4	4	4	6	6	6	8
Depth of welding (mm)	13	14	15	16	18	20	24	26	29	32.5

* Bracketed values are for PN 10 pipes

• Any specifications can change without prior notice.

• All information contained in this literature is given in good faith and believed to be accurate and reliable. But because of many factors which may be outside our knowledge and control and affect the use of product, no warranty is given or is to be implied with respect to such information, nor do we offer any warranty of immunity against patent infringement. No responsibility can be accepted for any error, omissions or incorrect assumptions.

The Supreme Industries Ltd. (Plastic Piping Division)
1161/1162, Solitair Corporate Park, Building No. 11,167,
Guru Hargovindji Marg, Chakala, Andheri Ghatkopar Link Road,
Andheri (East) Mumbai - 400 093. India. Tel: 91-22-6771 0000, 4043 0000
Fax: 6771 0099 / 4043 0099.
E-mail: pvc-pipes@supreme.co.in **Website:** www.supreme.co.in
Works : • Unit No.3, Gat No.47-48, at post Gadegaon, Tal.Jamner
Dist., Jalgaon. • D-101/102, MIDC, Jalgaon - 425 003.
Export Division: 91-22-6771 0126 / 4043 0126 Fax: 6771 0130
Overseas Office: Sharjah, U.A.E. Tel # + 971 6 557 4484;
Fax # + 971 6 557 4485

Branch Offices ☎ **Tel.** ☎ **Fax**

Ahmedabad	: 079 - 2768 1361	2768 0064
Bangalore	: 080 - 2667 3175	26673014
Chennai	: 044 - 39811180, 81	42132809
Cochin	: 0484 - 2385346	2385345
Hyderabad	: 040 - 66469558	23221120
Indore	: 0731 - 2432684	2432684
Jaipur	: 0141 - 3206123	2332134
Jalgaon Gadegaon	: 0257 - 3050541,42	3050611
Kanpur	: 0512 - 2332276	2332276
Kolkata	: 033 - 24858837, 39	25858838
New Delhi	: 011 - 46542023	26413174

Authorised Distributor

